




SS-M-220 Series



Quality Product

All Manufactured modules are tested 100% by EL (Electroluminescence) during the Production Process & Free from micro cracks.

Our high-performance modules are highly efficient, reliable and provide optimal output.

The company manufactures solar modules in compliance with global standard including MNRE, IEC 61215, 61730-1, 61730-2, 61701, UL 1703, UL 61730, ISO 9001:2008 & ISO 14001:2004 & 18001:2007.

High Efficiency .

High Module efficiency is obtaining top performance even in diffused light conditions.

We are leaders in providing our customers with maximum sunlight conversion.

Application Possibilities

Residential and Commercial rooftops, Car ports, Solar Farming, Balconies, Awnings, Street lights, Fences, and Canopies.

Our Team

We have a team of qualified experts and engineers making sure that modules produce maximum power. We pride ourselves in caring for each individual customer needs with detailed attention. Our end goal is to give a highly efficient product with exceptional customer service.

Guarantee

Our product is durable and has 25 years performance warranty. Integrated manufacturing of cells & modules in production line guarantees optimum performance.

US OFFICE:
Sonali Energies USA LLC
111 Charlotte Place Suite 101A
Englewood Cliffs, NJ 07632
Office Tel: 201-568-1424





SS-M-220 Series

Electric Performance Parameter

Model	SS-M-220
Nominal Maximum Power (Pmax/W)	220
Optimum Operating Voltage (Vmp/V)	38.3
Optimum Operating Current (Imp/A)	4.96
Open Circuit Voltage (Voc/V)	44.35
Short Circuit Current (Isc/A)	5.22
* Measurement Power Tolerance on Power 0 / +%	
* Under Standard Test Conditions (STC) of irradiance of 1000W/m ²	
* Normal Operating cell Temperature (NOCT) of irradiance of 800W/m ² , 43± 2° C	
* Spectrum AM 1.5 and cell temperature of 25 °C	
* Maximum System Voltage: 1000v IEC/UL	

Mechanical Parameter

Module Dimensions	1000 X 1050 X 30 mm / 39.37 X 41.34 X 1.18 inch
Weight	12 kgs / 26.45 lbs
Cell Size (Monocrystalline)	72.8x182 mm/2.87x7.17 in
No Of Cell	65 (5 X 13)
Junction Box	IP65 with Bypass diodes
Solar Cable	900mm (35.43inch) length with 4mm ²
Connectors	MC4 compatible / IP67
Glass (Tempered & Low Iron)	3.2mm (0.125in) ARC
Encapsulate	EVA
Back Cover	Composite Sheet
Frame	Anodized Aluminum Alloy

Temperature Coefficient

Coefficient of Current	+0.035% /°C
Coefficient of Voltage	-0.28% /°C
Coefficient of Power	-0.38% /°C


Tested Operating Conditions

Temperature Cycling Range	-40°C to 85°C
Humidity Freeze, Damp Heat	85% RH

Product Warranty

Product Warranty	12 Years
Performance Warranty	10 Years up to 90%, and 25 years up to 80%

Module Drawing



IV Curve

